








RoHS



■ SPECIFICATIONS









- Voltage rating : 250V AC, DC
- Current rating : 3A AC, DC.
- Withstanding voltage : 1000V AC/minute
- Insulation resistance : 1000MΩ min.
- Temperature range : - 40°C to + 105°C
- Contact resistance : 20mΩ max.
- Suitable JVT2508T series Terminal
JVT2508W series Wafer

■ HOUSING

- Material : Nylon 66 UL94-V0
- Q' ty : 02~10P 2,000 pcs/bag
11~15P 1,000 pcs/bag
- *is the key control size

JVT2508HNO-XXL

Logo
Series NO.
Housing
NO-PA66 UL94V-0
Lock
Pin NO.



02P

03P

04P

05~15P

Poles	DIM			Poles	DIM		
	A	B	C		A	B	C
02	2.50	7.3	5.64	09	20.00	24.8	23.14
03	5.00	9.7	8.14	10	22.50	27.3	25.64
04	7.50	12.3	10.64	11	25.00	29.8	28.14
05	10.00	14.7	13.14	12	27.50	32.3	30.64
06	12.50	17.3	15.64	13	30.00	34.7	33.14
07	15.00	19.8	18.14	14	32.50	37.3	35.64
08	17.50	22.3	20.64	15	35.00	39.8	38.14

Version	A1	弹片加胶	20220414	CLYDE	GENERAL TOLERANCE 0 ±0.35 .0 ±0.30 .00 ±0.20 .000 ±0.10
Content of change			Date	Signature	Unit



Approved by	Check	Design	Standard	2.5mm HSG with Lock
LI	CLYDE	LU	P/N	JVT2508HNO-XXL
			Map title	031
			Version	A1

A

B

C

D

E

F

G

H