



PIN OUT

P1	P2	P1	P2
A1	B1	B1	A1
A2	B2	B2	A2
A3	B3	B3	A3
A4	B4	B4	A4
A5	B5	B5	A5
A6	B6	B6	A6
A7	B7/B12	B7	A7/B12
A8	B13	B8	A13
A9	B14	B9	A14
A10	B15	B10	A15
A11	B16	B11	A16
A12	B17	B12	A17
A13	B18	B13	A18

ELECTRICAL CHARACTER:

- a. 100% OPEN&SHORT TESTING;
- b. WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- c. INSULATION RESISTANCE:10M Ohm(Min);
- d. CONDUCTIVE RESISTANCE:2 Ohm(Max).

NO.	PART NAME	PART NO	SPEC DESCRIPTION	QT'Y	UNIT
8	ACETATE TAPE	AQ-3-MS77001	W=25±5mm,BLACK	A/R	mm
7	LATCH	AQ-3-MS21008	STAINLESS STEEL	1	PCS
6	PCBA	AQ-3-MS31019	MINI SAS 36PIN PCB, PIN:15u" Au, 105±10 ohm	1	PCS
5	MOLDING	AQ-3-GL100401	PBT+30GF% BLACK	A/R	KG
4	MOLDING	AQ-3-GL100101	LDPE ROHS	A/R	KG
3	ASSEMBLY PARTS	AQ-3-MS62001	ASSEMBLY PARTS (Zinc ALLOY HOODS, HOOK,PULL-TAB, RUBBER RING)	1	set
2	PCBA	AQ-3-MS31021	MINI SAS 26P PCBA, PIN,15u Au, 100±10 Ohm	1	PCS
1	CABLE	AQ-3-MS41602	(28AWG*2C+D+HMAM+HM)*8C+M+AM+B,OD:7.5±0.15MM,BLACK PVC,100±5 Ohm	A/R	mm

AO	INITIAL RELEASE		14/08/30	
REV	DESCRIPTION OF CHANGE		DATE	
TOLERANCE		DIKWAN® DONGGGUAN AIQUN INDUSTRIAL CO., LTD.		
INCHES				
.X	.015			.30
.XX	.010			.10
M/M		SCALE NONE UNIT MM		
.XXX	.005	.05	REV AO	
DRAWN BY	TONY CHAN		SHEET 1/2	
CHECK BY			DATE 14/08/30	
APPD BY			CUSTOMER: DWG NO.:LT14-373	
P/N:			TITLE: MINI SAS 36P TO 26P	
		P/N: AQ-1-MS211012000		