



NOTE:
 1.100%OPEN&SHORT TESTIGN.
 2.INSULATION RESISTANCE 10M Ωhm MIN DC300V
 3.CONDUCTIVE RESISTANCE: 2 Ωhm MAX

NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QTY	UNIT
10	LABLE	AQ-5-MS5039	W6*L24. PRINT *P1&P2&P3&P4*	4	pcs
9	CDNN.	AQ-3-GL51S03	4P,NATURAL,PH5.08,PIN:G/F	4	pcs
8	CDNN.	AQ-3-GL51S01	SAS 29P/F,PIN:G/F	4	pcs
7	CABLE	AQ-3-MS40108	20AWG (RED/BLACK/YELLOW)	A/R	mm
6	ACETATE TAPE	AQ-3-MS77001	W=25±5mm,BLACK	1	pcs
5	MOLDING	AQ-3-GL145201	45P PVC BLACK	A/R	g
4	MOLDING	AQ-3-GL100101	LDPE,NATURAL	A/R	g
3	ASSEMBLY PARTS	AQ-3-MS62002	MINISAS HD ASSEMBLY (Zinc ALLOY HOODS, HOOK,PULL-TAB, RUBBER RING)	1	set
2	PCB	AQ-3-MS31021	MINISAS HD 4X PCB, PIN,15u&30U Au, 100±10 Ωhm	1	pcs
1	CABLE	AQ-3-MS41602	(28AWG*2C+D+HMAM+HM)*8C+M+AM+B,DD:7.5±0.15MM,BLACK PVC 100±5 Ωhm	A/R	mm

REV	DESCRIPTION OF CHANGE	DATE															
A	INITIAL RELEASE	12/10/12															
<table border="1"> <tr> <th colspan="3">TOLERANCE</th> </tr> <tr> <th>INCHES</th> <th colspan="2">MM</th> </tr> <tr> <td>.X</td> <td>.015</td> <td>.30</td> </tr> <tr> <td>.XX</td> <td>.010</td> <td>.10</td> </tr> <tr> <td>.XXX</td> <td>.005</td> <td>.05</td> </tr> </table>			TOLERANCE			INCHES	MM		.X	.015	.30	.XX	.010	.10	.XXX	.005	.05
TOLERANCE																	
INCHES	MM																
.X	.015	.30															
.XX	.010	.10															
.XXX	.005	.05															
DIKWAN® DONGGGUAN AIQUN INDUSTRIAL CO.,LTD.																	
DRAWN BY	TONY CHAN	SCALE NONE															
CHECK BY		UNIT MM															
CUSTOMER P/N:	P/N: AQ-1-MS454P12000	SHEET 1/1															
		DATE 16/04/10															
		DWG NO:															
		TITLE: MINISAS HD 4X TO 4*29P+4P															