


NOTE:
 1.100%OPEN&SHORT TESTIGN,
 2.INSULATION RESISTANCE 10M Ohm MIN DC300V
 3.CONDUCTIVE RESISTANCE: 2 Ohm MAX



13	LATCH	AQ-3-MS21008	STAINLESS STEEL	2	pcs
12	MOLDING	AQ-3-GL100101	LDPE,NATURAL	A/R	g
11	MOLDING	AQ-3-GL100401	PBT+30GF% BLACK	A/R	g
10	PCBA	AQ-3-MS31019	MINI SAS 36PIN PCB, PIN:15u Au, 105±10 ohm	2	PCS
9	EXPANDD	AQ-3-MS76001	PET BALCK DD: 10mm	A/R	mm
8	MOLDING	AQ-3-GL10501	PA BLACK	A/R	g
7	ACETATE TAPE	AQ-3-MS77001	W=25±5mm	A/R	mm
6	PCB	AQ-3-MS31023	MINI SAS HD 4I PCB(A/B),PIN: AU 15u&30u,100±10 ohm	1	PCS
5	PCB	AQ-3-MS31022	MINI SAS HD 4I PCB(C/D),PIN: AU 15u&30u,100±10 ohm	1	PCS
4	COVER	AQ-3-MS64002	MINI SAS HD 4I PC BLACK	1	PCS
3	HOUSING	AQ-3-MS64001	MINI SAS HD 4I PC BLACK	1	PCS
2	CABLE	AQ-3-MS20101	30AWG CABLE	A/R	mm
1	CABLE	AQ-3-MS40206	<30AWG*2C+2d>*Al+MYLAR,DD:0.97*2.17MM,100±10 ohm	A/R	mm

A	INITIAL RELEASE			12/1
REV	DESCRIPTION OF CHANGE			DA
TOLERANCE		INCHES	MM	DIKWAN® DONGGUAN AIQUN INDUSTRIAL CO.,
.X	.015	.30		
.XX	.010	.10		
.XXX	.005	.05		
DRAWN BY	TONY CHAN	SCALE	NONE	REV
		UNIT	MM	
CHECK BY		SHEET	1/1	CUSTOMER:
		DATE	16/04/10	DWG NO:
		TITLE: MINISAS 36P TO HD 4I RA		