


NOTE:
 1.100% OPEN & SHORT TESTIGN,
 2.INSULATION RESISTANCE 10M Ωhm MIN
 DC300V
 3.CONDUCTIVE RESISTANCE: 2 Ωhm MAX



FORWARDS

13	LABLE	AQ-5-MS5039	W7*L25, PRINT "P1&P2&P3&P4"	4	PCS
12	EXPANDO	AQ-3-MS76001	PET BALCK DD: 10mm	A/R	mm
11	LATCH	AQ-3-MS21008	STAINLESS STEEL	4	PCS
10	CONN.	AQ-3-GL51S01	SATA 7P/F,PIN:G/F	4	PCS
9	MOLDING	AQ-3-GL145201	45P PVC BLACK	A/R	9
8	MOLDING	AQ-3-GL100101	LDPE,NATURAL	A/R	9
7	MOLDING	AQ-3-GL10501	PA BLACK	A/R	9
6	ACETATE TAPE	AQ-3-MS77001	W=25±5mm	A/R	mm
5	PCB	AQ-3-MS31023	MINI SAS HD 4I PCB(A/B),PIN:AU 15u&30u,100±10 ohm	1	PCS
4	PCB	AQ-3-MS31022	MINI SAS HD 4I PCB(C/D),PIN:AU 15u&30u,100±10 ohm	1	PCS
3	COVER	AQ-3-MS64002	MINI SAS HD 4I PC BLACK	1	PCS
2	HOUSING	AQ-3-MS64001	MINI SAS HD 4I PC BLACK	1	PCS
1	CABLE	AQ-3-MS40206	(30AWG*2C+2d)*AL+MYLAR,DD:0.97*2.17MM,100±10 ohm	A/R	mm
NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QT'Y	UNIT

A	INITIAL RELEASE			13/03/02
REV	DESCRIPTION OF CHANGE			DATE
TOLERANCE INCHES		M/M		DIKWAN ® DONGGUAN AIQUN INDUSTRIAL CO., LTD. SCALE NONE UNIT MM SHEET 1/1 DATE 22/06/27 TITLE: MINI SAS HD 4i TO 4*SATA SE
.X	.015	.30	REV A	
.XX	.010	.10		
.XXX	.005	.05		
DRAWN BY	TONY CHAN		CUSTOMER. P/N:	P/N: AQ-1-MS331S10500
CHECK BY				