



NOTE:
 1.100% OPEN&SHORT TESTING,
 2.INSULATION: 10M Ohm MIN DC: 300V
 3.CONDUCTIVE: 2 Ohm MAX
 4.100% FUNCTIONAL TESTING

						A	INITIAL RELEASE			18/08/10			
						REV	DESCRIPTION OF CHANGE			DATE			
6	CONN	AQ-3-GL52B01	DB9/F,G/F	1	pcs	TOLERANCE INCHES MM			DIKWAN [®] DONGGUAN AIQUN INDUSTRIAL CO.,LTD				
5	SCREW	AQ-3-GL21007	SREW,Ø2.3*20mm	2	pcs	.X	.015	.30					
4	CONN.	AQ-3-GL52601	USB A/M,G/F	1	pcs	.XX	.010	.10					
3	MOLDING	AQ-3-GL100101	LDPE	A/R	9	.XXX	.005	.05	SCALE	NONE		REV	A
2	MOLDING	AQ-3-GL145201BK	45P PVC,BLACK	A/R	9	DRAWN BY	TONY CHAN		UNIT	MM		SHEET	1/1
1	PCBA	AQ-3-DB31003	PCBA,FR4,FT232+ZT213,W13.5*L35*T1.2mm	1	PCS	CHECK BY			DATE	18/08/10	DWG NO:	TITLE: DB9/F-USB ADAPTER	
NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QT'Y	UNIT	CUSTOMER P/N:			P/N: AQ-1-CV116DF01				