


ELECTRICAL CHARACTER:

- a. 100% OPEN&SHORT TESTING;
- b. WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- c. INSULATION RESISTANCE:10M Ohm(Min);
- d. CONDUCTIVE RESISTANCE:2 Ohm(Max).



13	MOLDING	PA BLACK	A/R	g		
12	COVER	MINI SAS HD 4i PC BLACK	2	PCS		
11	HOUSING	MINI SAS HD 4i PC BLACK	2	PCS		
10	PCB	MINISAS HD 4i PCB(C/D),PIN:AU 15u&30u,100±10 ohm	2	PCS		
9	PCB	MINISAS HD 4i PCB(A/B),PIN:AU 15u&30u,100±10 ohm	2	PCS		
8	EXPANDO	PET BALCK OD: 10mm	A/R	M		
7	ACETATE TAPE	W=25±5mm	A/R	M		
6	MOLDING	LDPE,NATURAL	A/R	g		
5	MOLDING	PBT+30GF% BLACK	A/R	g		
4	PCB	SIMSAS 8i 74P PCB,PIN:AU 15U&30u, 88±8 ohm	1	PCS		
3	LATCH	STAINLESS STEEL	1	PCS		
2	CABLE	30AWG OD:0.7mm	A/R	M		
1	CABLE	32AWGx2C+2D+al.mylay+amylay, OD:0.62x1.53, 85±5 ohm	A/R	M		
NO.	名称	描述	Q'TY	UNITS		
TOLERANCE						
INCHES		M/M				
.X	.015	.30	DIKWAN [®] DONGGUAN OIKWAN INDUSTRIAL CO., LTD.			
.XX	.010	.10				
.XXX	.005	.05				
DRAWN BY	TONY CHAN	SCALE	NONE		REV	A0
		UNIT	MM			
CHECK BY	LJF	SHEET	1/1	COSTOMER:		
		DATE	20/03/06	DWG NO.:M1703-0321A		
APPD BY		TITLE: SLIMSAS 8i TO 2*MINISAS HD 4i				
CUSTOMER. P/N:		P/N: A-1-MSA32010500				