



NOTE:
1.100% OPEN&SHORT TESTIGN,
2.INSULATION RESISTANCE: 10M Ohm MIN DC300V
3.CONDUCTIVE RESISTANCE: 2 Ohm MAX

NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QTY	UNIT
12	CABLE	AQ-3-MS40108	20AWG (RED/BLACK/YELLOW)	A/R	mm
11	LABLE	AQ-5-MS5039	W6*L24. PRINT *P1&P2&P3&P4*	4	pcs
10	CONN.	AQ-3-GL51S03	4P,NATURAL,PH5.08,PIN:G/F	4	pcs
9	CONN.	AQ-3-GL51S01	SAS 29P/F,PIN:G/F	4	pcs
8	EXPANDD	AQ-3-MS76001	PET BALCK DD: 10mm	A/R	mm
7	ACETATE TAPE	AQ-3-MS77001	W=25±5mm, BLACK	2	pcs
6	MOLDING	AQ-3-GL145201	45P PVC BLACK	A/R	9
5	MOLDING	AQ-3-GL100101	LDPE,NATURAL	A/R	9
4	MOLDING	AQ-3-GL100401	PBT+30%GF BLACK	A/R	9
3	LATCH	AQ-3-MS21008	STAINLESS STEEL	5	pcs
2	PCB	AQ-3-MS31019	SLIMSAS 4I PCB, PIN:AU 15u&30u, 88±8 ohm	1	PCS
1	CABLE	AQ-3-MS40208	<32AWG*2C+2d)*AL+MYLAR,DD:0.67*1.54MM,85±5 ohm.	A/R	mm

A		INITIAL RELEASE		12/10/12																															
REV	DESCRIPTION OF CHANGE			DATE																															
<table border="1"> <tr> <th colspan="2">TOLERANCE</th> <th colspan="2"></th> <th colspan="2"></th> </tr> <tr> <td></td> <td>INCHES</td> <td>MM</td> <td colspan="3"></td> </tr> <tr> <td>.X</td> <td>.015</td> <td>.30</td> <td colspan="3"></td> </tr> <tr> <td>.XX</td> <td>.010</td> <td>.10</td> <td colspan="3"></td> </tr> <tr> <td>.XXX</td> <td>.005</td> <td>.05</td> <td colspan="3"></td> </tr> </table>						TOLERANCE							INCHES	MM				.X	.015	.30				.XX	.010	.10				.XXX	.005	.05			
TOLERANCE																																			
	INCHES	MM																																	
.X	.015	.30																																	
.XX	.010	.10																																	
.XXX	.005	.05																																	
DIKWAN® DONGGGUAN AIQUN INDUSTRIAL CO., LTD.																																			
DRAWN BY	TONY CHAN	SCALE	NONE	REV	A																														
		UNIT	MM																																
CHECK BY		SHEET	1/1	CUSTOMER:																															
		DATE	16/04/10	DWG NO:																															
CUSTOMER P/N:		P/N: AQ-1-MS954P10500																																	