



NOTE:
 1.100%OPEN&SHORT TESTIGN,
 2.INSULATION RESISTANCE 10M Ohm MIN DC300V
 3.CONDUCTIVE RESISTANCE: 2 Ohm MAX

| P1/P2 | P1 | P2 | P3 | P4 | P5 | P6 | P7 | P8 | P9 | | P12 | P13 | P14 | P15 |
|----------|------|----|----|----|--------|--------|----|----|-----------|--|-----|-----------|-----|-----|
| P3/P4 | ---- | | | | P4P5P6 | P7P8P9 | | | P10P11P12 | | | P13P14P15 | | |
| SYMBOL | ---- | | | | GND | 5V | | | GND | | | 12V | | |
| WIRE AWG | ---- | | | | 20AWG | 20AWG | | | 24AWG | | | 20AWG | | |

| | | | | | | |
|------------------------|-----------------------|-------------------------------|--|----------------|-----|---|
| A | INITIAL RELEASE | | 20/03/16 | | | |
| REV | DESCRIPTION OF CHANGE | | DATE | | | |
| TOLERANCE INCHES MM | | | | | | |
| .X | .015 | .030 | DIKWAN® DONGGGUAN AIQUN INDUSTRIAL CO., LTD. | | | |
| .XX | .010 | .010 | | | | |
| .XXX | .005 | .005 | | | | |
| DRAWN BY | TONY CHAN | SCALE | NONE | ⊕ | REV | A |
| | | UNIT | MM | | | |
| CHECK BY | | SHEET | 2/2 | CUSTOMER: | | |
| | | DATE | 22/03/16 | DWG No.:AQ1617 | | |
| CUSTOMER P/N: | | TITLE:SLIMSAS 8I to SAS 68P+4 | | | | |
| | | P/N: AQ-1-MSA7H2P20500 | | | | |