



NOTE:  
 1.100% OPEN&SHORT TESTING,  
 2.INSULATION: 10M Ωhm MIN DC: 300V  
 3.CONDUCTIVE: 2 Ωhm MAX  
 4.100% FUNCTIONAL TESTING



NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QT'Y	UNIT	CUSTOMER P/N:	P/N: AQ-1-DB11601
7	CONN	AQ-3-GL52B01	DB9/M,G/F	1	pcs	A	INITIAL RELEASE
6	SCREW	AQ-3-GL21007	SREW,φ2.3*37mm	2	pcs	REV	DESCRIPTION OF CHANGE
5	CONN.	AQ-3-GL52601	USB A/M,G/F	1	pcs	TOLERANCE	
4	MOLDING	AQ-3-GL100101	LDPE	A/R	9	INCHES	
3	MOLDING	AQ-3-GL145201BK	45P PVC,BLACK	A/R	9	MM	
2	PCBA	AQ-3-DB31002	PCB WHIT FT232RL+ZT213CHIP,W13.5*L27.5*T1.2mm	1	PCS	.X .015 .30	
1	CABLE	AQ-3-DT40402BK	<28AWG*1P*AL+24AWG*2C>*AL+B;DD:5.0MM,BLACK PVC	A/R	mm	.XX .010 .10	
						.XXX .005 .05	
						DRAWN BY TONY CHAN	
						CHECK BY	
						SCALE NONE	
						UNIT MM	
						SHEET 1/1	
						DATE 18/08/10	
						REV A	
						CUSTOMER:	
						DWG NO:	
						TITLE: DB9/M-USB	
						P/N: AQ-1-DB11601	

**DIKWAN**® DONGGUAN AIQUN INDUSTRIAL CO., LTD