


RJ45 8P8C Pinout

P1	P2
PIN1	1 CTS
PIN2	2 DSR
PIN3	3 RXD
PIN4	4 GND
PIN5	5 GND
PIN6	6 TXD
PIN7	7 DTR
PIN8	8 RTS



NOTE:
 1.100% OPEN&SHORT TESTING,
 2.INSULATION: 10M Ohm MIN DC: 300V
 3.CONDUCTIVE: 2 Ohm MAX
 4.100% FUNCTIONAL TESTING

NO	NAME	Description	QTY	Unit
6	MOLDING	45P PVC, BLUE, MOLDED, ROHS	1	PCS
5	MOLDING	LDPE, MOLDED, ROHS	A/R	G
4	CONN.	USB C MALE, TC, ROHS	1	PCS
3	PCB	PCBA WITH FT232+ZT213 CHIP, ROHS	1	PCS
2	CONN.	RJ45 MALE, 8P8C, PIN G/F,	1	PCS
1	CABLE	28AWG*8C, BARE COPPER, BLUE PVC JACKET, ROHS	A/R	M

A	INITIAL RELEASE		16/03/02
REV	DESCRIPTION OF CHANGE		DATE
TOLERANCE			
INCHES		M/M	
.X	.015	.30	
.XX	.010	.10	
.XXX	.005	.05	
DRAWN BY		TONY CHAN	
CHECK BY			
CUSTOMER. P/N:		P/N: AQ-1-RJ10101B1800	

DIKWAN® DONGGUAN AIQUN INDUSTRIAL CO., LTD

SCALE: NONE UNIT: MM

SHEET: 1/3 CUSTOMER: [Symbol] REV: A

DATE: 16/9/20 DWG NO.:

TITLE: USB C TO RJ45