



NOTES:
 1.100% OPEN&SHORT WITH MISS WIRE TEST
 2.TEST CONDITION:
 1).CONDUCTANCE RESISTANCE:2 ohm
 2).SHORT OPEN DETERMINANT:20K ohm
 3).INSULATION RESISTANCE:10M ohm AT DC300V.

8	LATCH	AQ-3-MS21008	STAINLESS STEEL	4	pcs
7	LABLE	AQ-5-MS5039	W7*L25, PRINT "P1&P2&P3&P4"	8	pcs
6	ACETATE TAPE	AQ-3-MS77001	W=25±5mm	2	pcs
5	EXPANDD	AQ-3-MS76001	PET BALCK DD: 10mm	A/R	mm
4	MOLDING	AQ-3-GL100101	LDPE,NATURAL	A/R	g
3	MOLDING	AQ-3-GL145201	45P PVC BLACK	A/R	g
2	CONN.	AQ-3-GL51S01	SATA 7P/F,PIN:G/F	8	PCS
1	CABLE	AQ-3-MS40208	(30AWG*2C+2d)*AL+MYLAR,DD:0.97*2.17MM,100±5 ohm	A/R	mm
NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QT'Y	UNIT

A	INITIAL RELEASE		25/07/14			
REV	DESCRIPTION OF CHANGE		DATE			
TOLERANCE			DIKWAN® DONGGGUAN AIQUN INDUSTRIAL CO., LTD.			
INCHES						
MM						
.X	.015	.030	SCALE	NONE	REV	A
.XX	.010	.010	UNIT	MM		
.XXX	.005	.005	SHEET	1/1	CUSTOMER:	
DRAWN BY	TOMY CHANG		DATE	25/07/14	DWG No.:AQ14119	
CHECK BY			TITLE:4xSATA RA to 4xSATA RA			
CUSTOMER P/N:			P/N: AQ-1-MSSS4RR0500			