



**ELECTRICAL CHARACTER:**

- a. 100% OPEN&SHORT TESTING;
- b. WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- c. INSULATION RESISTANCE:10M Ohm(Min);
- d. CONDUCTIVE RESISTANCE:2 Ohm(Max).
- e.Impedance: 85 Ohm
- f.Electrical and mechanical performance should meet the PCIe5.0 industrial standard.

7	EXPANDO	PET, BLACK, OD:10mm	A/R	M
6	ACETATE TAPE	W=25±5mm, BLACK	A/R	M
5	MOLDING	PA, BLACK	A/R	g
4	COVER	MC10 4X, PA66+20%GF	1	PCS
3	PCB	MC10 4X PCB, .88±8 ohm	1	PCS
2	LATCH	STAINLESS STEEL	2	PCS
1	CABLE	SAS CABLE :30AWGx2C+2D+AL. My1ay+Amy1ay, 85±10ohm	A/R	M
NO.	PART NAME		Q'TY	UNITS
		TOLERANCE		
		INCHES	M/M	
.X		.015	.30	
.XX		.010	.10	
.XXX		.005	.05	
DRAWN BY		TONY CHAN	SCALE	NONE
CHECK BY			UNIT	MM
APPD BY			SHEET	1/1
CUSTOMER. P/N:			DATE	23/11/02
P/N:		AMSFF0010001	DWG NO.:	AQ1607-0214A
			TITLE:	MC10 4X TO MC10 4X
			CUSTOMER:	
			REV	A0

OIKWAN • 东莞市尚群实业有限公司  
DONGGUAN AIQUN INDUSTRIAL CO., LTD.