

Product Manual(TDS)

Epoxy acrylate BW L860M

Product introduction

BW L860M is a modified epoxy acrylate. It has the characteristics of leveling, low yellowing and good surface dryness. Mainly used in nail polish color glue layer, UV ink, UV wood, and has good interlayer adhesion and toughness, made into a colloid can show crystal transparent.

Product characteristics

Functional	2	Hardness	-
Active Ingredient (%)	100%	Proportion (25°C)	1.29
Appearance (25°C)	Transparent clear liquid	Shrinkage(%)	-
Viscosity (cps at 25°C)	1,500 - 3,000	Refractive Index(n_d at 25°C)	1.54
Color (APHA)	≤ 60	Elongation At Break (%)	-
Acid Value (mg KOH/g)	≤ 4	Tensile Strength (MPa)	-

- Low yellowing;
- Good leveling;
- Good surface dryness;
- Good pigment wettability;

Applications

- It is used in LED UV nail polish color layer, UV ink, UV wood coating.

Packaging

- In 20 kg plastic drums
- In 200 kg metal drums

Storage

- Store in a properly sealed container, away from sunlight and heat;
- At normal room temperature storage conditions, the product storage stability of at least 6 months;
- Low temperature or long-term storage, this product may form a false plastic layer;
- This rheological change can be restored by stirring or slight heating (Maximum temperature 45°C);

It is especially suggested that the above data and suggestions are based on experimental data, but due to the uselessness of users, we can not provide any guarantee for the integrity and accuracy of the information.

We recommend that customers choose our products and adopt them. Determine their applicability before making our recommendations.

