

Product Manual(TDS)

Urethane acrylate BW L415

Product introduction

BW L415 is an aliphatic polyurethane acrylate with high elongation, especially suitable for adhesives, pressure-sensitive adhesives, nail polish and hand feeling paint, etc. It has good adhesion and viscosity strength to various plastic, glass, metal and etc. materials.

Product characteristics

Functional	2	Hardness	-
Active Ingredient (%)	100%	Proportion (25°C)	1.02
Appearance (25°C)	Transparent clear liquid	Shrinkage(%)	-
Viscosity (cps at 60°C)	20,000 - 45,000	Refractive Index(nd at 25°C)	1.46
Color (APHA)	≤ 60	Elongation At Break (%)	645
Acid Value (mg KOH/g)	≤ 1	Tensile Strength (MPa)	13

- High tensile strength;
- Good flexibility;
- Excellent hydrolysis resistance;
- Good adhesive

Applications

- It is used in UV adhesion, UV nail polish, UV PSA.

Packaging

- In 20 kg plastic drums
- In 200 kg metal drums

Storage

- Store in a properly sealed container, away from sunlight and heat;
- At normal room temperature storage conditions, the product storage stability of at least 6 months;
- Low temperature or long-term storage, this product may form a false plastic layer;
- This rheological change can be restored by stirring or slight heating (up to 45°C);

It is especially suggested that the above data and suggestions are based on experimental data, but due to the uselessness of users, we can not provide any guarantee for the integrity and accuracy of the information. We recommend that customers choose our products and adopt them. Determine their applicability before making our recommendations.

