

Product Manual(TDS)

Urethane Acrylate BW L426D

Product introduction

BW L426D is a Polyurethane Acrylate with low viscosity and good toughness. It has the characteristics of low crystallinity, good hardness, fast curing speed, and is easy to clean etc. It is widely applied in UV 3D printing, UV nail polish, UV ink, etc, providing good printing accuracy and tensile strength.

Product characteristics

Functional	2	Hardness	-
Active Ingredient (%)	100%	Proportion (25°C)	1.23
Appearance (25°C)	Transparent clear liquid	Shrinkage(%)	-
Viscosity (cps at 60°C)	20,000 - 30,000	Refractive Index(nd at 25°C)	1.52
Color (APHA)	≤ 60	Elongation At Break (%)	-
Acid Value (mg KOH/g)	≤ 1	Tensile Strength (MPa)	-

- High strength;
- Easy to clean and wash;
- Fast curing speed;
- Good hardness;

Applications

- It is applied in UV nail glue, UV ink, and 3D printing.

Packaging

- In 20 kg plastic drums
- In 200 kg metal drums

Storage

- Store in a properly sealed container, away from sunlight and heat;
- At normal room temperature storage conditions, the product storage stability of at least 6 months;
- Low temperature or long-term storage, this product may form a false plastic layer;
- This rheological change can be restored by stirring or slight heating (up to 45°C);

It is especially suggested that the above data and suggestions are based on experimental data, but due to the uselessness of users, we can not provide any guarantee for the integrity and accuracy of the information. We recommend that customers choose our products and adopt them. Determine their applicability before making our recommendations.

