

Product Manual(TDS)

Urethane acrylate BW L430

Product introduction

BW L430 is a polyurethane acrylate with high transparency, fast curing speed, high hardness and excellent tensile strength. It is widely used in light curing 3D printing, UV nail polish and UV ink, providing good toughness and yellowing resistance for the paint film.

Product characteristics

Functional	3	Hardness	-
Active Ingredient (%)	100%	Proportion (25°C)	1.16
Appearance (25°C)	Transparent clear liquid	Shrinkage(%)	-
Viscosity (cps at 60°C)	3000-6000	Refractive Index(nd at 25°C)	1.50
Color (APHA)	≤60	Elongation At Break (%)	-
Acid Value (mg KOH/g)	≤1	Tensile Strength (MPa)	-

- Good weathering resistance;
- High hardness;
- Fast curing speed;
- Good tensile strength

Applications

- It is used in UV 3D printing, UV nail polish and UV ink.

Packaging

- In 20 kg plastic drums
- In 200 kg metal drums

Storage

- Store in a properly sealed container, away from sunlight and heat;
- At normal room temperature storage conditions, the product storage stability of at least 6 months;
- Low temperature or long-term storage, this product may form a false plastic layer;
- This rheological change can be restored by stirring or slight heating (Maximum temperature 45°C);

It is especially suggested that the above data and suggestions are based on experimental data, but due to the uselessness of users, we can not provide any guarantee for the integrity and accuracy of the information.

We recommend that customers choose our products and adopt them. Determine their applicability before making our recommendations.

A 广州市番禺区番禺大道北555号天安节能科技园产业大厦1座904

904. NO. 1 Building, Tianan Hi- tech Ecological Park.No.555 panyu road North, Panyu,Guangzhou

T 020- 3107 4363 F 020- 3107 4309 E contact@bawo-chem.com W www.bawo-chem.com Factory : Guangdong · Yingde

无锡公司&研发中心: 江苏无锡市锡山开发区科技创业园

制造基地地址: 广东英德市东华镇高新技术产业园



抖音号



视频号



公众号