

Product Manual(TDS)

Urethane acrylate BW L8450H

Product introduction

BW L8450H is an aliphatic polyurethane acrylate with low energy curing system of LED UV lamp; it has the characteristics of low shrinkage, low exothermic, good toughness, excellent transparency, etc.; it is mainly used in the extension layer of nail polish and has the characteristics of good toughness, high transmittance, non-yellowing phase and so on, with excellent appearance.

Product characteristics

Functional	2	Hardness	86D
Active Ingredient (%)	100%	Proportion (25°C)	1.09
Appearance (25°C)	Transparent clear liquid	Shrinkage(%)	-
Viscosity (cps at 60°C)	10000-18000	Refractive Index(nd at 25°C)	1.49
Color (APHA)	≤60	Elongation At Break (%)	-
Acid Value (mg KOH/g)	≤1	Tensile Strength (MPa)	-

- Low heat release;
- High transmittance;
- Good toughness;

Applications

- It is used in LED UV nail polish extension layer,UV ink, UV adhesives.

Packaging

- In 20 kg plastic drums
- In 200 kg metal drums

Storage

- Store in a properly sealed container, away from sunlight and heat;
- At normal room temperature storage conditions, the product storage stability of at least 6 months;
- Low temperature or long-term storage, this product may form a false plastic layer;
- This rheological change can be restored by stirring or slight heating (Maximum temperature 45°C);

It is especially suggested that the above data and suggestions are based on experimental data, but due to the uselessness of users, we can not provide any guarantee for the integrity and accuracy of the information.

We recommend that customers choose our products and adopt them. Determine their applicability before making our recommendations.



抖音号



视频号



公众号