



Smart Mini DC UPS

AKDCE Series



AKDCE-212



AKDCE-415/430



AKDCE-860/1660

For more information on AoKu Energy products,
please visit: www.aokuenergy.com

Smart Mini DC UPS

▼ Main Features

- High capacity lithium batteries, provides long backup to the loads.
- High compatibility, suitable for most digital products in the market.
- POE can transmit power and simplify wiring.
- Intelligent circuit design with over-charging, over-discharging and short circuit protections.
- Built-in adapter allows wide AC voltage range (100~240Vac).
- Solar panel is acceptable for the input interface.



MODEL	AKDCE-															
	212		415		415P		430P		430M		430S		860		1660	
INPUT																
Input voltage		100–240Vac														
OUTPUT																
DC output voltage(optional)		USB 1.5A 9/12V 1A	5V+USB 2A 9V/12V 1A 12V 1A	5V+USB 2A 9V/12V 1A 15V/24V (POE) 0.5A	5V+USB 2A 9V/12V 2A 15V/24V (POE) 1A	5V+USB 2A 9V/12V 2A 12VX4 2A	5V+USB 2A 9V/12VX4 2A Solar input 1A	5V+USBX2 2A 9/12V 2A 15V/24V(POE) 1A 12VX4 5A Solar input 2A								
Voltage select		Choosing through the slide switch														
Output power (Max)		12W		15W			30W					60W				
Transfer time		0 ms														
BATTERY																
Battery type		Lithium battery														
QTY. & capacity of battery		6700mAh		8800mAh								2200mAhX8 2200mAhX16				
CHARGE																
Charging period		1–2 hours		2–3 hours								4–5 hours				
PHYSICAL																
Unit dimension (mm)		141.5*84.5*35		180*106*29								258*152*46				
Net weight (Kg)		0.3		0.4								0.94		1.28		
ENVIRONMENT																
Environment of performance		Temperature: 0℃℃–40℃, Humidity: 20%–90%														
Noise level		Less than 40dB														