

AKDCE Series 18W / 36W / 60W



▼ Main Features

- High capacity lithium batteries, provides long backup to the loads.
- High compatibility, suitable for most digital products in the market.
- POE can transmit power and simplify wiring.
- Intelligent circuit design with over-charging, over-discharging and short circuit protections.
- Built-in adapter allows wide AC voltage range (85~265Vac).



AKDCE Series 18W / 36W / 60W



■ Technical Parameter

MODEL	AKDCE 1830				AKDCE 1860				AKDCE 3660				AKDCE 6060				
INPUT																	
Input voltage	100-240Vac /50Hz~60Hz																
OUTPUT																	
Output power(Max.)	18W				18W				36W				60W				
Output	USB C / DC1	DC2	DC3	POE	USB A / USB C/DC1	DC2	DC3-4	POE	USB A+ USB C+DC1	DC2	DC3-4	POE	USB A+ USB C+DC1	DC2	DC3-4	POE	
Output voltage Vdc (selectable)	5V	9V	12V	24V	5V	9V	12V	24/48V	5V	9V	12V	24/48V	5V	9V	12V	24/48V	
Output current & power	2A 10W	1A 9W	1A 12W	0.4A 9.6W	2A 10W	1A 9W	1A 12W	0.4A /0.2A 9.6W	2.4A 12W	2A 18W	3A 36W	1A/0.4A 24W	2.4A 12W	2A 18W	5A 60W	1A/0.4A 24W	
QTY.& capacity of battery	8000mAh				16000mAh				16000mAh				20000mAh				
CHARGE																	
Charging period	Typical: 2-3 Hours																
PHYSICAL																	
Unit dimension(mm)	160 * 105 * 31.5				177 * 117 * 32				177 * 117 * 32								
Net weight(Kg)	0.4				0.58				0.62								
ENVIRONMENT																	
Environment of performance	Temperature 0°C-40°C,Humidity 20%-90%																
Noise level	Less than 40dB																